




ALUMINIUM UNIVERSAL BOLT TERMINAL CONDUCTOR TO FLAT UNIVERSAL

Issue No.	5	EUCF
Issue Dt.	2022.04.02	
Doc. Rev. No.	0	
Doc. Rev. Dt.	-	
MATERIAL OF TERMINAL - ALUMINIUM ALLOY GRADE 4600 CONFORMING IS 617-1994 (LM-6). MATERIAL OF NUT, BOLT, PLAIN WASHER - MILD STEEL HOT DIP GALVANISED SPRING WASHER SPRING STEEL ELECTRO GALVANISED.		
TERMINAL SUITABLE FOR < 245 kV		



H	C		W
H1=11Ø	C1=25.0	C5=50.0	W1= 80
H2=14Ø	C2=32.0	C6=55.0	W2=100
H3=18Ø	C3=40.0	C7=32.0, 40.0, 44.50, 50.0	W3=120
	C4=44.5	C9=CUSTOM MADE	

CATALOG No.	TYPE	CONDUCTOR RANGE	DIMENSIONS - mm.			
		AA Ø mm.	X	T	Y	J
EUCF-6	A-II	10.00 - 16.00	72	12	60	10
EUCF-7	A-I	16.00 - 18.05	72	12	60	10
EUCF-9	A-I	18.00 - 22.26	72	12	60	10
EUCF-11B	B,C	22.00 - 26.00	72	12	74	10
EUCF-11C	B,C	26.00 - 28.13	76	12	74	10
EUCF-13B	B,C	28.00 - 30.15	76	12	74	10
EUCF-13C	B,C	30.00 - 32.00	76	12	74	10

NOTE :

- PLEASE ADD SUFFIX H1, H2, H3 AS REQUIRED FOR DIAMETER OF 4 HOLES H DIA. IN THE TERMINAL FOR e.g. CATALOG NO. OF TERMINAL FOR CONDUCTOR DIA. 10.0 TO 16.0 mm. WITH 14 mm. HOLE DIA IS EUCF-6_H2
- PLEASE ADD SUFFIX C1, C2, ..., C6 AS REQUIRED FOR CENTRE TO CENTRE DISTANCE OF 4 HOLES IN THE TERMINAL PAD. IN CASE OF CUSTOM MADE PLEASE SPECIFY NUMERICAL VALUE FOR e.g.

B-30/31, Nand Bhuvan Industrial Estate, Mahakali Caves Road, Andheri (E), Mumbai 400 093, INDIA

Phone: 91-22-2821 3764, 2831 3764 Fax: 91-22-2835 2795

E-mail : sales@exalt.co.in Web site : <https://exalt.co.in/>



ALUMINIUM UNIVERSAL BOLT TERMINAL CONDUCTOR TO FLAT UNIVERSAL

Issue No.	5	EUCF
Issue Dt.	2022.04.02	
Doc. Rev. No.	0	
Doc. Rev. Dt.	-	

FOR STANDARD ITEMS :

CATALOG NO. OF TERMINAL FOR CONDUCTOR DIA. 10.0 TO 16.0 mm WITH 14mm HOLE DIA. HOLE TO HOLE CENTRE 50mm. IS EUCF-6_H2_C5

FOR CUSTOM MADE ITEMS :

CATALOG NO. OF TERMINAL FOR CONDUCTOR DIA. 10.0 TO 16.0 mm WITH 14mm HOLE DIA. HOLE TO HOLE CENTRE 42mm IS EUCF-6_H2_42

- 3) PLEASE ADD SUFFIX W1, W2, W3 AS REQUIRED FOR WIDTH OF TERMINAL. e.g. CATALOG NO. OF TERMINAL FOR CONDUCTOR DIA. 10.0 TO 16.0 mm WITH 14mm HOLE DIA. HOLE TO HOLE CENTRE 50mm. TERMINAL WIDTH 80mm. IS EUCF-6_H2_C5_W1
- 4) VALUES IN THE CATALOG IS SUITABLE FOR W=80mm VALUES WILL DIFFER IF W CHANGES.
- 5) PLEASE ADD SUFFIX SS FOR CLAMPS WITH STAINLESS STEEL NUT BOLTS e.g. CATALOG NO. OF TERMINAL FOR CONDUCTOR DIA. 10.0 TO 16.0 mm WITH 14mm HOLE DIA. HOLE TO HOLE CENTRE 50mm. TERMINAL WIDTH 80mm. WITH STAINLESS STEEL NUT BOLTS IS EUCF-6_H2_C5_W1_SS
- 6) PAD MOUNTING HARDWARE IS OBTAINED FROM CATALOG TYPES EHBG, EHNG, EHFG, EHWG FOR GALVANISED SCREWING HARDWARES. AND EHBS, EHNS, EHCNS, EHFS, EHWS FOR STAINLESS STEEL SCREWING HARDWARES.

B-30/31, Nand Bhuvan Industrial Estate, Mahakali Caves Road, Andheri (E), Mumbai 400 093, INDIA

Phone: 91-22-2821 3764, 2831 3764 Fax: 91-22-2835 2795

E-mail : sales@exalt.co.in Web site : <https://exalt.co.in/>